

Hanging scales KERN HCB



KERN HCB



Convenient for hanging loads

- Features**

 - Multi data hold function:
By pressing the Hold key...
 - the weight display can be „frozen“ for 5 sec
 - the weight display can be „frozen“ until any key is pressedWhen the weighing value remains unchanged...
 - the weight display is automatically „frozen“ for 5 sec
 - the weight display is automatically „frozen“ until any key is pressed
 - LCD display, digit height 12 mm
- HCB:**

 - Peak load display (peak hold), measuring frequency 5 Hz
 - Ready for use: 3x 1.5V AA standard, operating time approx. 300 h
- Optional Extras**

 - Hook (stainless steel) included, aperture approx. 25 mm, can be reordered, **KERN HCB-A02**
 - Snap link included (stainless steel) with safety catch, aperture approx. 15 mm, can be reordered, **KERN HCB-A01**

STANDARD

CAL EXT

UNIT

IP 65

INOX

MOVE

BATT

TARE

STANDARD

1 DAY

2 YEARS
GUARANTY

OPTION

DKD
+3 DAYS

Model	Weighing range [Max] kg	Read-out [d] g	LCD display, digit height mm	Dimensions housing WxDxH mm	Height with hook and snap link mm	Net weight approx. kg	Optional Extra		
							DKD Calibr. Certificate		
KERN							DKD	KERN	
HCB 20K10	20	10	12	150x80x45	290	0,4	☐	963-128	
HCB 20K50	20	50	12	150x80x45	290	0,4	☐	963-128	
HCB 50K20	50	20	12	150x80x45	290	0,4	☐	963-128	
HCB 50K100	50	100	12	150x80x45	290	0,4	☐	963-128	
HCB 99K50	99	50	12	150x80x45	290	0,4	☐	963-129	
HCB 100K200	100	200	12	150x80x45	290	0,4	☐	963-129	
HCB 200K100	200	100	12	150x80x45	290	0,4	☐	963-129	
HCB 200K500	200	500	12	150x80x45	290	0,4	☐	963-129	